

# Magnet Care Sheet

## Before Attaching Magnet

- **Never bend or fold** as this may result in permanent damage. The magnet must remain completely flat. Bends or bubbles in the Magnet may allow air to lift it from the surface of the vehicle.
- Ensure that the surface area of the vehicle is completely **free of dust, dirt, grease or other contaminate**. A dirty surface will hinder adhesion.
- Vehicle must also be **dry** before attaching the magnet.
- Apply a good quality **car wax** to the area of the vehicle where the magnet will be placed.

## Applying Magnet

- Magnets **should not cover body moldings** or extend beyond the contours of the vehicle.
- Magnets will **not** adhere to irregular or highly curved surfaces. The surface must be flat.
- The magnet must be **flat against the surface**, with no air pockets, bubbles, or edges of the sign raised off the surface.
- Magnets will **not** adhere to vehicle surfaces that are of non-metallic composition (i.e. fiberglass, high-density plastic, etc).

## Cleaning and Storage of Magnet

- To clean your new magnetic sign, use a **wet soapy sponge and wipe gently**.
- **Do not immerse the sign in water** or take it through a car wash!
- High temperatures may cause it to warp or deteriorate. **Do not store inside a hot car**.
- To store, place your magnet on a **flat smooth metal surface** and keep in a **cool place!**